

MATERIAL SAFETY DATA SHEET

Magnesium Turnings

1. Product Identification

Product Name	:	Magnesium Turnings
Synonyms	:	Magnesium ribbon, magnesium clipping, magnesium turnings
CAS No.	:	7439-95-4
Molecular Weight	:	24.31
Chemical Formula	:	Mg

2. Composition/Information on Ingredients

Magnesium Metal 98% - 99%

3. Hazards Identification

Emergency Overview

WARNING! FLAMMABLE SOLID. MAY CAUSE IRRITATION TO SKIN, EYES, AND RESPIRATORY TRACT

Hazardous Material Identification System (Ratings provided for your reference, scale 0 - 4)

Health Rating: 1 - Slight (Life)

Flammability Rating: 3 - Severe (Flammable)

Reactivity Rating: 3 - Severe (Water Reactive)

Contact Rating: 2 - Moderate

Lab Protective Equip: GOGGLES ; PROPER GLOVES; CLASS D EXTINGUISHER

Storage Color Code: Red Stripe (Store Separately)

Potential Health Effects

Inhalation: Inhalation of dusts or fumes may irritate the respiratory tract and may cause metal fume fever.

Symptoms may include coughing, chest pain, fever, and leukocytosis.

Ingestion: Magnesium metal does not have well-characterized toxicity. May cause abdominal pain and diarrhea.

Skin Contact: Particles embedded in the skin may cause eruptions. Molten magnesium may cause serious skin burns

Eye Contact: High concentrations of dust may cause mechanical irritation. Watching a magnesium fire can cause eye injury.

Chronic Exposure: No information found.

Aggravation of Pre-existing Conditions: Existing wounds contaminated with magnesium are very slow to heal.

4. First Aid Measures

Inhalation: Remove to fresh air. Get medical attention for any breathing difficulty.

Ingestion: If swallowed, Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact: Remove any contaminated clothing. Wash skin with soap or mild detergent and water for at least 15 minutes. Get medical attention if irritation develops or persists.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get medical attention if irritation persists.

MATERIAL SAFETY DATA SHEET

Magnesium Turnings

5. Fire Fighting Measures

Fire: Autoignition temperature: 473C (883F)

When heated in air to a temperature near its melting point, magnesium may ignite and burn. Dangerous in the form of dust or flakes, and when exposed to flame or by violent chemical reaction with oxidizing agents. Magnesium may react with moisture or acids to evolve hydrogen gas, which is a highly dangerous fire or explosion hazard. Autoignition temperature is for Magnesium turnings or ribbon.

Explosion: Fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Minimum explosible concentration 0.030 grams/liter. Water used on molten magnesium will produce hydrogen gas and may cause an explosion.

Fire Extinguishing Media:

Use metal extinguishing powders such containing Ternary Eutectic Chloride, powdered talc, dry graphite, powdered sodium chloride, soda ash, or dry sand. Warning! Do not use foam, chlorinated products such as Halon®, carbon dioxide, or water to extinguish magnesium fires, because dangerous reactions will occur. Use of water on molten magnesium will produce hydrogen gas and may cause an explosion.

Special Information: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Fire fighters should protect their eyes and skin from flying particles. In order to prevent eye injury, do not look directly at magnesium fires.

6. Accidental Release Measures

Remove all sources of ignition. Ventilate the area of the spill or leak. Wear appropriate personal protective equipment as specified in Section 8. Collect the spilled material and transfer to a clean, dry metal covered container for recovery or disposal. Do not use water in the collection process.

If the spilled magnesium has come into contact with water, proceed with caution. Hydrogen gas may be generated, which may cause a fire or explosion. Evacuate the area, put on fire fighting protective equipment and proceed as with a metal fire.

7. Handling and Storage

Keep in tightly closed container. Store in a cool, dry, ventilated area. Protect against physical damage. Store finely divided powder, chips or shavings in detached fire-resistant building, protected from moisture and away from oxidizers, chlorine, bromine, iodine, acids, and all possible sources of ignition. Heavier sections may be stored in the open. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits: None established.

Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area.

Personal Respirators (NIOSH Approved): For conditions of use where exposure to dust or mist is apparent and engineering controls are not feasible, a particulate respirator (NIOSH type N95 or better filters) may be worn. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-face positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection: Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: Silver solid.
Odor: Odorless.
Solubility: Insoluble in water.
Specific Gravity: 1.74 @ 20C (68F) (solid)
pH: No information found.
% Volatiles by volume @ 21C (70F): 0
Boiling Point: 1100C (2012F)
Melting Point: 649C (1200F)
Vapor Density (Air=1): No Information found
Vapor Pressure (mm Hg): 1.0 @ 621C (1150F)
Evaporation Rate (BuAc=1): No Information found

10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage. Slowly oxidizes in moist air.

Hazardous Decomposition Products:

Toxic gases and vapors may be released if involved in a fire.

Hazardous Polymerization: Will not occur.

Incompatibilities: Magnesium reacts dangerously with many substances, including oxidizers, carbonates, cyanides, chlorinated hydrocarbons, sulfates, acids, and other metals. Please refer to the NFPA publication "Fire Protection Guide on Hazardous Materials" most recent edition for details. Reacts with acids to form hydrogen gas.

Conditions to Avoid: Moisture, heat, flames, ignition sources and incompatibles.

11. Toxicological Information

No LD50/LC50 information found relating to normal routes of occupational exposure

Cancer Lists	---NTP Carcinogen---		
	Known	Anticipated	IARC
Ingredient			
Magnesium Metal (7439-95-4)	No	NO	None

12. Ecological Information

Environmental Fate: No information found.

Environmental Toxicity: No information found.

MATERIAL SAFETY DATA SHEET

Magnesium Turnings

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: MAGNESIUM Hazard Class: 4.1

UN/NA: UN1869

Packing Group: III

International (Water, I.M.O.)

Proper Shipping Name: MAGNESIUM Hazard Class: 4.1

UN/NA: UN1869

Packing Group: III

International (Air, I.C.A.O.)

Proper Shipping Name: MAGNESIUM Hazard Class: 4.1

UN/NA: UN1869

Packing Group: III

15. Regulatory Information

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols: F

Risk Phrases: R 11 Highly flammable. R 15 Contact with water liberates extremely flammable gases.

Safety Phrases: S 7/8 Keep container tightly closed and dry. S 43A In case of fire, use dry chemical (never use water).

WGK (Water Danger/Protection) CAS# 7439-95-4: Not available

Canada CAS# 7439-95-4 is listed on Canada's DSL List US Federal

TSCA CAS# 7439-95-4 is listed on the TSCA Inventory

NOTE

Although the information in this MSDS was obtained from sources which we believe to be reliable, it cannot be guaranteed. In addition, this information may be used in a manner beyond our knowledge or control. The information is, therefore, provided without representation or warranty express or implied.